

PRODUCT SPECIFICATION



Reinforce Paper Printed Tape - 260

260 is a heavy duty grade, reinforced water activated tape. The product is available in natural and white.

Construction

Papers	Top Sheet: 25# natural or 30# white high strength virgin kraft Bottom Sheet: 23 lbs/ream mg natural high strength virgin kraft
Laminating Adhesive	14.5# high melt index polypropylene based copolymer.
Water Activated Adhesive	15# chemically grafted starch based copolymer adhesive, designated as S3911
Reinforcement	Pattern: Lengthwise threads with diamond cross-machine pattern Lengthwise Threads: 4.27 Lb. (2-1-1-1-2) 75 Fiberglass (per 72mm), 1/2" spacing Cross-Machine Threads: 1.45 Lb. (1-1-1) 150 Fiberglass, 1.10" spacing, 43 degree angle
Caliper	7.0 mils

Performance

	Tensile Data 260 Tan 260 White	Machine Direction 83 lbs/in 83 lbs/in	Cross Machine Direction 30 lbs/in 30 lbs/in		
Sizes & Put-ups					
	Size	Rolls/Carton	Rolls/Carton		
	72mm x 375	8	75		
	72mm x 450'	10	60		
	72mm x 500'	6	90		
	Please call our sales service department for custom sizes and put-ups				

Personalized Packaging Systems[™] - 991 Ehlers Road, Neenah, WI 54956 USA Info@PersonalizedPackagingSystems.com • ⁺1 (920) 720-3500