

# SPECIFICATION SHEET



## 1.9 mil hi-tack Polypropylene - Printed Tape - 6600 series

Hot melt adhesives satisfy over 90% of all carton-sealing requirements. Excellent corrugate adhesion and quick tack properties make hot melt tapes ideal for most applications while offering reduced packaging costs. Consistent release tension allows for optimal performance on case sealing machinery.

	Unit	Range	PP 6600 CLEAR	PP 6601 TAN	PP 6602 WHITE
Film Thickness	(mils)	(± 1.5%)	1.16	1.16	1.16
Total Thickness	(mils)	(± 1.5%)	1.93	1.93	1.93
Tensile Strength	(lbs/in)	(±3.3)	26	26	26
Elongation at Break	(%)	(±25)	165	165	165
Adhesion to steel	(oz/in)	(±10)	32	32	32
Loop-Tack	(oz/in)	(min.)	45	45	45
Holding Power to Fiberboard	(minutes)		1000+	1000+	1000+
Service Temp.- minimum	(degrees F)		-15°F	-15°F	-15°F
Service Temp.- maximum	(degrees F)		100°F	100°F	100°F
Application Temp. - minimum	(degrees F)		20°F	20°F	20°F
Application Temp. - maximum	(degrees F)		110°F	110°F	110°F